

## Luxmeter “TKA-ПКМ” (31)



### Main technical data and characteristics


<b>Illumination</b> measurement range	10 ÷ 200,000 lx
Basic relative error of illumination measurements (no more)	± 8.0%
Including the limits of the permissible relative error caused by the nonlinearity of the sensitivity of the device (no more)	± 3.0%
Including the limits of the permissible relative error caused by the deviation of the relative spectral sensitivity from the relative spectral luminous efficiency (no more)	± 5.0%

Including the limits of the permissible relative error caused by the deviation of the calibration by source A (no more)	± 3.0%
Including the limits of the permissible relative error caused by the spatial characteristic of the photometric head of the luxmeter (no more)	± 5.0%
The limits of the additional relative error of the device when measuring optical quantities, due to a change in the sensitivity of the photometric head when the air temperature in the measurement zone changes for every 10 ° C (no more)	± 3.0%
Liquid crystal display	3½ digit

### Overall dimensions of the device

Measuring unit (no more)	130 x 70 x 30 mm
Photometric head (no more)	Ø40 x 30 mm
Device weight (no more)	0.22 kg
Battery – Krona battery standard size	9 in

The difference in the function of the relative spectral sensitivity of the photodetector was corrected by a system of light filters to match the function of the relative spectral luminous efficiency of monochromatic radiation for daytime vision  $V(\lambda)$  in accordance with GOST 8.332. The effective reference plane of the Luxmeter coincides with the front plane of the cosine attachment of the photodetector. ❌ ❌



A well-proven light meter, reliable and easy to operate. Affordable price.